

DIVISION 12 - FURNISHINGS**12-00-00 Furnishings**

- A. Furniture layouts by consultants are required. Coordinate with district representative/project manager/director to base layout on actual furniture to be purchased/provided.
- B. The owner will provide all furniture, unless otherwise directed.
- C. Student art should be de-mountable
- D. Furniture should be comfortable, varied, low maintenance and durable.
- E. Furniture seating shall allow for movement while seated (i.e. pivoting, rocking, cantilever, etc.).
- F. Furniture should be designed to be ergonomic.
- G. Meet the requirements of LEED for Schools Low-Emitting Materials requirements. Furniture evaluation: New furniture and furnishing items must be tested in compliance with ANSI/BIFMA Standard Method M7.1-2011. Comply with ANSI/BIFMA e3-2011 Furniture Sustainability Standard, Sections 7.6.1 and 7.6.2, using either the concentration modeling approach or the emissions factor approach. Model the test results using the open plan, private office, or seating scenario in ANSI/BIFMA M7.1, as appropriate. For classroom furniture, use the standard school classroom model in CDPH Standard Method v1.1. Documentation submitted for furniture must indicate the modeling scenario used to determine compliance. SCS Indoor Advantage and SCS Indoor Advantage and Gold are acceptable certifications to demonstrate compliance.
- H. Salvaged and reused furniture more than one year old at the time of use is considered compliant, provided it meets the requirements for any site-applied paints, coatings, adhesives, and sealants.

12-10-00 Art

- A. Preserve/protect art during construction.

12-20-00 Window Treatment

- A. Typically, provide monolithic horizontal, heavy duty, commercial, manually operated roller shades with opacity for sun/glare/heat control and room darkening as required by space and orientation.
- B. PVC free shades preferred. Example products: Hunter Douglas Nysan Interior Shades, Mechoshade, Draper, Roll-A-Shade.
- C. Do not provide vertical or horizontal blinds.

12-21-13 Horizontal Roller Shades

- A. These are the preference for new buildings and major renovations or where existing shades do not exist.
- B. If adjacent rooms have vertical or horizontal blinds, consider using horizontal roller shades with similar look for consistency on exterior.
- C. Opacity should be based on building orientation.
- D. 3% openness is a good base standard when uncertain of daylighting requirements.
- E. Provide manual operation unless approved. Use chain attached to side of jambs (not free hanging).

12-22-00 Curtain and Drapes

- A. Curtains are not recommended. They are typically not good for indoor air quality and the District does not have the maintenance capability of cleaning them. Where replacing to match existing, ensure fire resistance requirements are met.

12-40-00 Accessories

- A. File cabinets
1. Letter or legal, locking or non-locking, 2 or 4 drawers

12-48-13 Entrance Floor Mats and Frames

- A. Provide walk off mats at all entrances to the building.
1. Primary entrances include:
 - a. Public entrances
 - b. Staff entrances from parking lots.
 - c. Entrances from playgrounds, auxiliary buildings and athletic fields
 2. Secondary entrances include:
 - a. Back doors to classrooms, modulars
 - b. Service and maintenance doors
- B. At primary entrances size to be full width of opening and a minimum of 10 feet in the direction of travel (20 feet preferred).
- C. When possible, recess into the floor. Where not possible, provide aluminum frame meeting ADA requirements.
- D. Provide carpet with minimum 30 oz/sy weight.
- E. Walk off mats shall be removable and/or easily cleanable in place.
- F. Example products:
1. Outdoor mats: Milliken Obex Prior or Terga
 2. Indoor mats: Milliken Obex Terga or Forma mats or Waterhog Classic (waffle pattern).
 - 3.

12-50-00 Furniture

Modernized and new school construction:

See attached PPS Furniture Standards from School Specialty for Draft Standards.

Pre-k to 8th grade Student Chair

District currently uses the Scholar Craft series 150 solid plastic stack chair see colors and sizes on chart below

Chair Features:

- solid plastic seat back with handle
- color by size (see chart)
- steel glides (depends on floor finish)
- lumbar flex seat design
- stackable to 5 or 6 chairs
- no book pocket or ganging

Use	Seat height	Color	Weight
Pre- k	11.5	Red or Navy	14lb
K-1	13.5	Navy	14lb
2nd - 4th	15.5	gold or burgundy	16lb
5th - HS	17.5	Navy or brown	16lb
science lab	17.5	Navy	16lb
music room	17.5	Navy	16lb
computer lab	17.5	Navy	16lb

High School and Science Lab (Middle School, K-8) Chair

District currently uses Artco-Bell Discover product number D10A
18" seat height, steel glides, navy seat, char dark gray frame (2013)

Chair Features:

- solid plastic seat back with handle
- navy seat color
- steel glides
- lumbar flex seat design
- stackable to 5 or 6 chairs
- no book pocket or ganging

Student Desk and Activity Table Standard

District currently uses Virco series 7900 single and double desks, chrome and black legs, medium oak laminate top finish. Current sizes are single student desks, double student desks, half-moon group tables (36" x 72") 6-Place tables (36" x 72"), side or computer tables (30" x "72") (2013)

Desk/Table Features:

- Plywood top w/ high pressure finish
- Clear edge finish, no banding
- 40 pound weight limit for double student desks
- 20 pound weight limit for Single student desks
- 90 pound weight limit for 6 place tables (36" x 72")
- No book pocket on activity tables
- Adjustable legs (22" to 30")
- Adjustable legs (36" to 44")

Features that have been a problem in the past:

- rubber type trim as a finished edge (peels)
- laminate over particle board (very heavy)
- other leg styles (hard to clean around, not sturdy)

High School Combination Desk Standard

Currently using a variety of Virco and Scholar craft products. If more were purchased the best match for current inventory is the Scholar Craft 650 series desk, navy seat, 17.5" seat height, flat desk top (rectangle shape and pallet size).

- A. 4 student science table – solid black chemical resistant top, solid wood base without book storage pockets each side, used with standard height chairs (17.5” – 18” seat height)
 - 1. No plastic laminate tables only allowed with prior District approval due to durability and scratching issues.

Music Equipment Requirements:

- A. Manhasset Music Stands: Model M48
- B. Manhasset Storage Cart Model 1910
- C. Manhasset conductor stand: model 1401
- D. Wenger Band Chairs: Student chair (there are different sizes for different age levels).
- E. Wenger choir risers: 098D053 3-step Signature Riser, 203 lbs (92 kg) + 098D541 Siderails, Set of 2, 62 lbs (28 kg)

12-61-00 Fixed Auditorium Seating

- A. Seating should be durable and easy to clean and maintain.
- B. Define system components, fabrication and installation requirements for fixed seating and seating accessories in Auditorium.
- C. Theatre seating quantity in new high school construction shall be approximately 500. Confirm and coordinate with current District Educational Specifications.
- D. Seating width shall use default width of 21”, with 22” and 20” width allowed in order of preference to allow alignment of row ends. 19” wide seats shall be allowed only where completely unavoidable to align row ends.
- E. Seats may be gravity lift to $\frac{3}{4}$ vertical, with pushback pressure hinge to 100% vertical. IF spring assist lift is specified, then the specified models for all approved manufacturers shall be confirmed available and durable as spring assisted.
- F. Chairs shall be fully padded and upholstered for comfort. Minimum 2” back and minimum 3” seat bottom. Ergo foam is acceptable in lieu of serpentine spring foundation.
- G. Aisle End chairs shall have integral warm white LED aisle lighting fixtures for IBC .2FC compliance.
- H. Layout shall comply with latest applicable OSSC and ANSI 117.1 Accessibility requirements
- I. Basis of Design shall include not less than, but not significantly in excess of:
 - 1. Irwin “Citation”
 - 2. Seating Concepts BT250 Producer”
 - 3. Hussey Seating “Quattro Plush”

12-66-13 Telescoping Bleachers

- A. Gymnasium Bleachers
 - 1. Motorized telescopic type.
 - 2. Recycled plastic bench seating or wood. Wood preferred.
 - 3. Provide accessible seating per ADAAG and stairs/railings to meet ADA along aisles. Provide non-slip surface and contrasting edges.
 - 4. The outer edge handrails are to be permanently mounted to aisles and not removable.
 - 5. All other rails have to be removable for the middle sections.

6. End rails shall meet strength, height and pickets to meet guardrail requirements and shall also be permanently mounted.
7. Provide rounded/curved edges both above and below in undercarriage to prevent possible injury.
8. Provide front and side skirt boards anywhere there is an exposed end to prevent players/balls from sliding underneath the 1st Row.
9. Ensure wheels are sized to prevent marring flooring. Coordinate with floor finish.
10. Power operators with heavy duty motor or gear drives.
11. Provide metal cover over motor and wheels to protect chains from debris and provide a safety switch that if cover is taken off the power system will not work.
12. Integral safety switches with auto stop feature.
13. Pendant controls.
14. Mechanical / electrical locking system, "Schlage" keyed to building master.
15. Provide for audio/visual systems integration - Coordinate with District Athletics, IT and Electronics for location and type.
16. Provide minimum 5-year warranty including moving parts.
17. Example manufacturer - "Hussey" Seating Co., Irwin Telescoping Seating Company and Sheridan. Interkal, for self-storing aisle rail.

12-93-00**Site Furnishings**

- A. Site Furnishings
 1. General:
 - a. All site furnishings will need to be approved by the District.
 - b. Use recycled, local and sustainable materials when possible.
 - c. All site furnishings located in lawn shall sit on a concrete pad that acts as a mow strip and alleviates trimming and edging work.
 2. Picnic Tables and benches must meet the requirements of ADA.
 3. Trash and Recycling receptacles can only be provided with District approval. They must be chained down or permanently attached.
- B. Fencing, Gates and Bollards see 32-31-13